

The Original Eclipse

Emergency Eclipse



Ordering Information

SKU	Finish
EM807506	BN Brushed Nickel
EM807512	WH White
	ORB Oil Rubbed Bronze

Electrical

Voltage	110V - 120V
Dimmable	Yes

Battery

Battery / J-Box combo (708808/708810) is required for emergency operation, and must be installed as a part of the rough-in package.

Construction

Material	Steel
Diffuser/Lens	Easy Twist on/off Acrylic Lens
Backup Time	90 Minutes*
Test Switch	Single Pole
Self Recharge	24 Hours to Full Charge*

Qualifications

ETL Listed	Wet Location
Energy Star	Listed
DLC	Listed

*90 minute operation with required 708808/708810 battery combo, sold separately.

*To help prevent permanent damage to the EM as well as void in warranty, constant power must be run to the fixture prior to connecting the EM to the disc.

Item Number	Battery / J-Box Combo	Watts (W)	EM Watts	Voltage (V)	Outside Diameter	Height	Color (K)	CRI	Title 24
EM807506	708808	15	6	AC 120	7.4"	1.2"	30 K, 41K	80	Yes
EM807512	708810	30	12	AC 120	9.5"	1.2"	30 K, 41K	80	Yes



sales@elighting.net 972-231-8882

Product specifications are subject to change without notice.

Eclipse Battery Backup

Battery & J-Box Combo



Ordering Information

SKU	Watts	Pole	Compatible Fixture(s)
708808	15W	Single Pole	EM807506
708810	30W	Single Pole	EM807512

Qualifications

Safety Rated	Damp Location
Warranty	www.elighting.net/warranty
ETL	Listed
ADA	

Electrical

Voltage	110V - 120V
---------	-------------

Construction

Material	Steel

Dimensions

Width	8.5"
Height	2.95"
Length	4.33"



sales@elighting.net 972-231-8882

Product specifications are subject to change without notice.