

# Ultra Thin Round Eclipse

Emergency Eclipse



## Ordering Information

SKU	Finish
EM900502	<b>BN</b> Brushed Nickel
EM900510	<b>WH</b> White
EM900544	<b>ORB</b> Oil Rubbed Bronze

## Electrical

Voltage	110V - 120V
Dimmable	Yes

## Battery

Battery / J-Box combo (708812/708814) is required for emergency operation, and must be installed as a part of the rough-in package.

## Construction

Material	Steel
Diffuser/Lens	White Acrylic Lens
Backup Time	90 Minutes*
Test Switch	<b>Dual Pole</b>
Self Recharge	24 Hours to Full Charge*

## Qualifications

ETL Listed	Wet Location
Energy Star	Listed
DLC	Listed

\*90 minute operation with required 708812 battery J-Box combo, sold separately.

\*To help prevent permanent damage to the EM as well as void in warranty, constant power must be run to the fixture prior to connecting the EM to the disc.

Item Number	Battery / J-Box Combo	Watts (W)	Initial Lumens	EM Watts	Voltage (V)	EM Lumens	Outside Diameter	Height	Color (K)	CRI
EM900502	708812	10	700	4	AC 120	240	5.5"	.625"	30K, 41K	90
EM900510	708812	15	1,050	6	AC 120	360	7"	.625"	30K, 41K	90
EM900844	708814	22.5	1,600	7	AC 120	400	7"	.625"	30K, 41K	90



sales@elighting.net 972-231-8882

Product specifications are subject to change without notice.

# Eclipse Battery Backup

Battery & J-Box Combo



## Ordering Information

SKU	Watts	Pole	Compatible Fixture(s)
708812	15W	Dual Pole	EM900510, EM900502
708814	30W	Dual Pole	EM900544

## Qualifications

Safety Rated	Damp Location
Warranty	<a href="http://www.elighting.net/warranty">www.elighting.net/warranty</a>
ETL	Listed
ADA	

## Electrical

Voltage	110V - 120V
---------	-------------

## Construction

Material	Steel

## Dimensions

Width	8.5"
Height	2.95"
Length	4.33"



[sales@elighting.net](mailto:sales@elighting.net) 972-231-8882

Product specifications are subject to change without notice.